



LED-775

Date: _____
Type: _____
Project: _____

General Description:

The LED-775 is a low profile narrow two-row LED Wraparound standard with an acrylic prismatic lens or the optional Lumieo[®] lens.


The specially formulated acrylic Lumieo[®] Lens provides excellent light transmission and diffusion of the LEDs.

Features and Benefits:

- High performance optical engine delivers main beam focus through the lens.
- Unique Lumieo[®] diffuser manages the balance of efficiency and aesthetics and helps hide the LEDs.
- Lumieo[®] is a premium white acrylic sheet which provides both high light transmission and excellent LED hiding capabilities.
The diffusion comes from a combination of a very fine surface texture and special diffusing additives.
- Linear arrayed LED modules provide diffused, but effective illumination.
- LED light engine by LG Innotek, or Keystone Technologies

Applications:

For surface commercial applications such as offices, hospitals, schools etc. Standard surface mounting, cable and pendant mounting accessories are available.



Notice: Dimensions and specifications subject to change without notice.

5-C MARLEN DRIVE, HAMILTON, NJ 08691
PHONE: 609-587-7900 FAX: 609-613-5586

WWW.MONMOUTHLIGHTING.COM



LED-775

Date: _____
 Type: _____
 Project: _____

LED 775		
LG Innotek driver and boards		
Specifications	2ft	4ft
Input Wattage	28.59	47.89
Delivered Lumens (lms)	2541.6	4420.7
Efficacy (LpW)	88.9	92.3
Color Rendering Index (CRI)	83.6	83.7
Color Temperature (CCT)°K	3500,4000	3500,4000
Minimum Ambient Temperature (°F)	-4	-4
Maximum Ambient Temperature (°F)	140	140
Dimming	0-10v	0-10v
Rated Life (L70)	50,000	50,000
Warranty	5 years	5 years
Voltage (V)	120-277V	120-277V
Operating Frequency (Hz)	50/60	50/60
UL	Yes	Yes
FCC	Compliant	Compliant

Values taken from LM-79 reports

IES photometric files available upon request.

Housing	Length	Color Temp	Driver/Board	Voltage	Options
LED-775	2ft	30 3000	LG LG Innotek	EBUNI (Multi Volt 120/277)	PL Prismatic Acrylic Lens WPL Engineered White Lens LL Lumieo [®] Lens NY 20 Gauge NYC Housing DM Dimming Ballast EMB Emergency Ballast
LED-775	4ft	35 3500			
		40 4000			
		50 5000			

Consult factory for additional options and accessories.

Notice: Dimensions and specifications subject to change without notice.